

AC axial fan

straight blades (A series)

Beijing Hengrui Mechanical and Electrical Equipment Co,Ltd
Phone +86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

Nominal data

Type	W2D210-EA10-22		
Motor	M2D068-CF		
Phase		3~	3~
Nominal voltage	VAC	400	480
Wiring		Y	Y
Frequency	Hz	50	60
Method of obtaining data		cs	cs
Valid for approval/standard		CE	CE
Speed (rpm)	min ⁻¹	2750	3250
Power consumption	W	87	130
Current draw	A	0.25	0.27
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	-	-

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



AC axial fan

straight blades (A series)

Technical description


Weight	4.3 kg
Size	210 mm
Motor size	68
Rotor surface	Painted black
Blade material	Sheet steel, painted black
Housing material	Die-cast aluminum, painted black
Guard grille material	Die-cast aluminum; steel, phosphated and coated with black plastic (RAL 9005)
Number of blades	5
Airflow direction	A; BS-AS
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent as per EN 60034-5
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	F2-2
Max. permitted ambient temp. for motor (transport/storage)	+ 60 °C
Min. permitted ambient temp. for motor (transport/storage)	- 15 °C
Installation position	Shaft horizontal
Condensation drainage holes	On rotor side
Mode	S1
Motor mounting	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
With cable	Lateral
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE
Approval	UL 1004-1; CSA C22.2 No. 100



AC axial fan


straight blades (A series)

Product drawing



1	Screw plug PG 13.5 (3x); tightening torque 1.9 Nm
2	Screw plug PG 11 (2x); tightening torque 1.9 Nm
3	Screw plug PG 36 (3x), tightening torque 3.9 Nm
4	Direction of air flow "A", BS-AS
5	Shown without housing cover
6	Terminal strip
7	Connection board for customer
8	PE

Connection diagram




Y	Star connection, three-phase motor
L1	black
L2	blue
L3	brown
PE	Green/yellow
TOP	not used



AC axial fan
straight blades (A series)

Curves: Air performance 50 Hz



Measurement: LU-42529-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values


	U	f	n	P _e	I	q _v	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	cfm	in. wg
1	400	50	2750	87	0.25	895	525	0.00

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow



AC axial fan
straight blades (A series)

Curves: Air performance 60 Hz



Measurement: LU-42531-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	cfm	in. wg
1	480	60	3250	130	0.27	1055	620	0.00

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow

