

ø250x77 mm (IP21 / IP55)

280.0~438.0 CFM



■ Specifications

Model	Bearing	Rating Voltage	Freq.	Power Current	Power Consumption	Speed	Air Flow	Static Pressure	Noise	Weight
	● VAPO ○ BALL ◎ Sleeve	(VAC)	(Hz)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dB(A))	(g)
CF4207HBL-10000-A99	○	100-240	50 / 60	0.36 / 0.20	16.5 / 17.5	2100	438.0	0.57	53.4	950
CF4207LBL-10000-A99	○	100-240	50 / 60	0.10 / 0.07	5.0 / 6.0	1350	280.0	0.27	41.2	900

Frame : PBT Plastic


Operation Temperature(°C) : -40°C ~+50°C

Safety : CE/TUV/UL/CUL




■ Function Two speed control : H99, HA9, HB9

■ Protection IP21 : AA9, HA9 IP55 : AB9, HB9

■ Air Flow-Static Pressure Characteristics



■ External Dimensions(mm)





Beijing Hengrui Mechanical and Electrical Equipment Co.,Ltd
+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

SUNON®

