

120x120x38 mm

93.0~138.0 CFM




■ Specification


	Bearing	Rated Voltage	Power Current	Power Consumption	Speed	Airflow	Static Pressure	Noise	Weight	Curve
	● VAPO	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H ₂ O)	(dB(A))	(g)	
MEC0381V1-000U-A99	●	12	833	10.0	3100	138.0	0.36	48.0	218.0	1
MEC0381V2-000U-A99	●	12	421	5.1	2600	116.0	0.26	44.0	218.0	2
MEC0381V3-000U-A99	●	12	241	2.9	2100	93.0	0.18	37.0	218.0	3
MEC0382V1-000U-A99	●	24	383	9.2	3100	138.0	0.36	48.0	218.0	1
MEC0382V2-000U-A99	●	24	224	5.4	2600	116.0	0.26	44.0	218.0	2
MEC0382V3-000U-A99	●	24	130	3.1	2100	93.0	0.18	37.0	218.0	3
Model	2BALL Sleeve	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H ₂ O)	(dB(A))	(g)	
EEC0381B1-000U-A99	☉	12	833	10.0	3100	138.0	0.36	48.0	214.0	1
EEC0381B2-000U-A99	☉	12	421	5.1	2600	116.0	0.26	44.0	214.0	2
EEC0381B3-000U-A99	☉	12	241	2.9	2100	93.0	0.18	37.0	214.0	3
EEC0382B1-000U-A99	☉	24	383	9.2	3100	138.0	0.36	48.0	214.0	1
EEC0382B2-000U-A99	☉	24	224	5.4	2600	116.0	0.26	44.0	214.0	2
EEC0382B3-000U-A99	☉	24	130	3.1	2100	93.0	0.18	37.0	214.0	3
EEC0384B1-000U-A99	☉	48	203	9.7	3100	138.0	0.36	48.0	214.0	1
EEC0384B2-000U-A99	☉	48	120	5.8	2600	116.0	0.26	44.0	214.0	2
EEC0384B3-000U-A99	☉	48	69	3.3	2100	93.0	0.18	37.0	214.0	3

■ Function R Type : F99 / F Type : G99

■ Air Flow-Static Pressure Characteristics



■ External Dimensions(mm)



※ All model could be customized. Please contact with Sunon Sales.

※ Specifications are subject to change without notice. Please Visit SUNON website at www.sunon.com for update information.