

# Meets GR487

For salt spray environment

Environmental Test : Meets GR-487-CORE(2000), Section3.34.1 Salt Fog Test Procedure.



| Size (mm) | Model               | Voltage (VDC) | Bearing 2 BALL | Speed (RPM) | Air Flow (CFM) | Static Pressure (Inch-H2O) | Noise (db(A)) | Weight (g) |
|-----------|---------------------|---------------|----------------|-------------|----------------|----------------------------|---------------|------------|
| 40x40x28  | GF40282BX-10000-SDP | 24            | ☉              | 17600       | 24.6           | 2.07                       | 58.1          | 46.0       |
|           | GF40282B1-10000-SDP | 24            | ☉              | 14600       | 20.4           | 1.41                       | 54.0          | 46.0       |
|           | GF40282B2-10000-SDP | 24            | ☉              | 13100       | 18.3           | 1.13                       | 51.7          | 46.0       |
|           | GF40282B3-10000-SDP | 24            | ☉              | 10500       | 14.7           | 0.73                       | 46.8          | 46.0       |
|           | GF40282BX-10000-QDP | 24            | ☉              | 17600       | 24.6           | 2.07                       | 58.1          | 46.0       |
|           | GF40282B1-10000-QDP | 24            | ☉              | 14600       | 20.4           | 1.41                       | 54.0          | 46.0       |
|           | GF40282B2-10000-QDP | 24            | ☉              | 13100       | 18.3           | 1.13                       | 51.7          | 46.0       |
|           | GF40282B3-10000-QDP | 24            | ☉              | 10500       | 14.7           | 0.73                       | 46.8          | 46.0       |
| 60x60x25  | GF60252BX-10000-SDP | 24            | ☉              | 12900       | 54.8           | 1.44                       | 55.4          | 84.0       |
|           | GF60252B1-10000-SDP | 24            | ☉              | 11500       | 48.8           | 1.23                       | 52.7          | 84.0       |
|           | GF60252B2-10000-SDP | 24            | ☉              | 9000        | 38.3           | 0.75                       | 48.9          | 84.0       |
|           | GF60252B3-10000-SDP | 24            | ☉              | 6450        | 27.4           | 0.38                       | 41.7          | 84.0       |
|           | GF60252BX-10000-QDP | 24            | ☉              | 12900       | 54.8           | 1.44                       | 55.4          | 84.0       |
|           | GF60252B1-10000-QDP | 24            | ☉              | 11500       | 48.8           | 1.23                       | 52.7          | 84.0       |
|           | GF60252B2-10000-QDP | 24            | ☉              | 9000        | 38.3           | 0.75                       | 48.9          | 84.0       |
|           | GF60252B3-10000-QDP | 24            | ☉              | 6450        | 27.4           | 0.38                       | 41.7          | 84.0       |
| 80x80x25  | GF80251B5-0000-AD9  | 12            | ☉              | 3200        | 41.0           | 0.18                       | 33.0          | 87.0       |
|           | GF80251B6-0000-AD9  | 12            | ☉              | 2900        | 37.0           | 0.15                       | 30.0          | 87.0       |
|           | GF80251B7-0000-AD9  | 12            | ☉              | 2600        | 33.0           | 0.11                       | 28.0          | 87.0       |
|           | GF80252B5-0000-AD9  | 24            | ☉              | 3200        | 41.0           | 0.18                       | 33.0          | 87.0       |
|           | GF80252B6-0000-AD9  | 24            | ☉              | 2900        | 37.0           | 0.15                       | 30.0          | 87.0       |
|           | GF80252B7-0000-AD9  | 24            | ☉              | 2600        | 33.0           | 0.11                       | 28.0          | 87.0       |
| 80x80x38  | GF80382BX-10000-SDP | 24            | ☉              | 10000       | 133            | 1.76                       | 64.3          | 235.0      |
|           | GF80382B1-10000-SDP | 24            | ☉              | 8000        | 107.3          | 1.14                       | 59.6          | 235.0      |
|           | GF80382BX-10000-QDP | 24            | ☉              | 10000       | 133            | 1.76                       | 64.3          | 235.0      |
|           | GF80382B1-10000-QDP | 24            | ☉              | 8000        | 107.3          | 1.14                       | 59.6          | 235.0      |
| 92x92x25  | GF92251B5-0000-AD9  | 12            | ☉              | 3000        | 51.5           | 0.15                       | 34.0          | 99.0       |
|           | GF92251B6-0000-AD9  | 12            | ☉              | 2700        | 45.0           | 0.13                       | 32.0          | 99.0       |
|           | GF92251B7-0000-AD9  | 12            | ☉              | 2400        | 39.5           | 0.10                       | 28.0          | 99.0       |
|           | GF92252B5-0000-AD9  | 24            | ☉              | 3000        | 51.5           | 0.15                       | 34.0          | 99.0       |
|           | GF92252B6-0000-AD9  | 24            | ☉              | 2700        | 45.0           | 0.13                       | 32.0          | 99.0       |
|           | GF92252B7-0000-AD9  | 24            | ☉              | 2400        | 39.5           | 0.10                       | 28.0          | 99.0       |
| 92x92x38  | GF92382BX-10000-SDP | 24            | ☉              | 9000        | 172.9          | 1.73                       | 66.8          | 260.0      |
|           | GF92382B1-10000-SDP | 24            | ☉              | 7200        | 145.3          | 1.2                        | 60.6          | 260.0      |
|           | GF92382BX-10000-QDP | 24            | ☉              | 9000        | 172.9          | 1.73                       | 66.8          | 260.0      |
|           | GF92382B1-10000-QDP | 24            | ☉              | 7200        | 145.3          | 1.2                        | 60.6          | 260.0      |

\* If you need special specification. Please contact Sunon sales.